

**absolute coatings, inc.**  
**PRODUCT INFORMATION**

**ABSCO**

**QUICK DRY POLYURETHANE SEALER**  
**Technical Data Sheet**

**PRODUCT DESCRIPTION**

ABSCO Quick Dry Sealer utilizes our unique Soya based formula to provide a pure urethane sealer of unique qualities. Designed to be used under all types of oil-based finishes, Quick Dry Sealer will help improve the durability of the entire job. **FOR PROFESSIONAL USE ONLY.**

**RECOMMENDED USES:** *Excellent for sealing most interior wood surfaces, including floors, doors, cabinets, furniture...*

Color in Container	Amber
Solids Content Weight	40%
Chemical Resistance	Excellent
VOC	550 g/l
Flash Point	105°F
	Sheen Not Applicable
	Freeze/Thaw Stability: Stable
Dry Time	Minimum 1-2 hours between coats with good conditions
Clean Up	Mineral Spirits
Viscosity	10 seconds (Zahn Cup #3)

**APPLICATION METHODS:** Good quality brush, or spray  
**COVERAGE:** Approx. 500 -600sq. feet per gallon on raw wood.  
**PACKAGING:** 1 gallon, 1 quart

**SURFACE PREPARATION:** proper surface preparation is essential to achieve a professional finish. Surface should be clean, dry and free from wax, grease, etc. If the old surface is cracked, remove completely by sanding; rinse with paint thinner and wipe clean.

**NEW OR NEWLY SANDED FLOORS:** Make several passes with the sandpaper, increasing paper fineness with each pass. The final pass before application of ABSCO QUICK DRYING POLYURETHANE PRIMER/SANDING SEALER should be with #100 grit screen or sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor with dust free cotton cloth dampened with mineral spirits.

**PREVIOUSLY SEALED OR FINISHED WOOD FLOORS:** All wax, grease, soaps, oil and soil must be removed thoroughly. Buff the floor with #100 screen disc. Remove all dust completely, as described above.

**absolute coatings, inc.**  
Wood Finishes for Professionals™

38 Portman Road New Rochelle, NY 10801

©2003, Absolute Coatings, Inc. In New York (914) 636-0700 Outside New York 1-800-221-8010 Fax (914) 636-0822

**EQUIPMENT:** Apply ABSCO QUICK DRYING POLYURETHANE PRIMER/SANDING SEALER with a lambswool or nylon applicator, or good quality brush.

**THINNING INSTRUCTIONS:** ABSCO QUICK DRYING POLYURETHANE PRIMER/ SANDING SEALER is ready to use from the can, no thinning necessary.

**DIRECTIONS:** Apply ABSCO QUICK DRYING POLYURETHANE PRIMER/SANDING SEALER with the grain of the wood. Apply when product and wood surface are at approximately 60° F.

**DRYING TIME:** Allow 1 hour dry time on new wood, up to two hours on succeeding coats. Sand lightly between coats if within 24 hours, sand thoroughly if longer than 24 hours between coats.

**CURING TIME:** ABSCO QUICK DRYING POLYURETHANE PRIMER/SANDING SEALER will be dry in 60-90 minutes, allow overnight drying for full use.

**COVERAGE:** Approximately 600-650 square feet per gallon, depending upon surface preparation.

**CLEAN-UP:** Use mineral spirits or paint thinner for cleaning tools.

#### **HEALTH AND SAFETY PRECAUTIONS**

VAPOR AND SPRAY MIST HARMFUL. MAY CAUSE DIZZINESS, HEADACHE, OR NAUSEA. HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION.

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Close container after each use. Use only with adequate ventilation. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

**First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

#### **LEGAL DISCLAIMER**

Manufacturer's Warranty: Absolute Coatings, Inc. and its distributors only obligation shall be to replace such quantity of the product proved to be defective. As a professional product, the user accepts full responsibility for the applicability of this product for their specific use. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith.