



Material Safety Data Sheet

Date of printing : 9/24/2004.
Version : 1.01

Date of issue : 9/24/2004.
Date of previous issue : No Previous Validation.

Section 1. Chemical product and company identification

Prepared For :

Prepared by
Akzo Nobel Coatings Inc.
25 Brush Street
Pontiac, MI 48341
1-(248)-637-0400

ATTN:

IN CASE OF EMERGENCY (HEALTH OR SPILLS):
CHEMTREC (US and Canada) (800) 424-9300

Product no. : 161000

Product - Class : Synteko Extra Semi Gloss

Customer Part Numbe :

Customer ShipTo ID:

Section 2. Composition, Information on Ingredients

Name	CAS #	% by weight	Vapor pressure	Exposure Limits (ACGIH-TLV/OSHA-PEL)
n-methyl pyrrolidone	872-50-4	1 - 5	0.04 kPa (0.3 mm Hg) (at 20°C)	Not available.
butoxyethoxyethanol	112-34-5	1 - 5	0.004 kPa (0.03 mm Hg) (at 20°C)	Not available.
1,2-propanediol	57-55-6	1 - 5	0.01 kPa (0.08 mm Hg) (at 20°C)	ACGIH TLV (United States). TWA: 50 ppm 8 hour(s).

Section 3. Hazards identification

Emergency overview : DANGER!

Effects of Overexposure : HARMFUL IF INHALED.
MAY CAUSE EYE IRRITATION.
CONTAINS MATERIAL WHICH MAY CAUSE BIRTH DEFECTS BASED ON ANIMAL DATA.
CONTAINS MATERIAL WHICH MAY CAUSE DAMAGE TO THE FOLLOWING ORGANS: BLOOD, KIDNEYS, LIVER, SKIN.

Avoid contact with eyes. Avoid breathing vapor or mist. Keep container closed. Use only with adequate ventilation. Avoid exposure during pregnancy. Wash thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eyes : Corrosive to eyes.
Other effects of eye contact may include : burning, tearing,

Skin : Practically non-toxic by skin absorption. Irritating to skin. May cause sensitization by skin contact.
Other effects of skin contact may include : dermatitis, discoloration, sensitization,

Inhalation : Harmful by inhalation. Moderately irritating to the respiratory system.

Ingestion : Toxic if swallowed. May cause burns to mouth, throat and stomach.

Potential chronic health effects : CARCINOGENIC EFFECTS: None by OSHA standard.
MUTAGENIC EFFECTS: None by OSHA standard.
TERATOGENIC EFFECTS: Classified POSSIBLE for human [N-METHYL PYRROLIDONE].
Contains material which may cause damage to the following organs: blood, kidneys, liver, skin.

Medical conditions aggravated by overexposure: : Not available.

NOTICE: Reports have associated repeated and prolonged OVEREXPOSURE to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents of this package may be harmful or fatal.

See toxicological information (section 11)

Section 4. First aid measures

- Eye Contact** : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
- Skin Contact** : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
- Inhalation** : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
- Ingestion** : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Section 5. Fire fighting measures

- Flammability of the product** : May be combustible at high temperature.
- Auto-ignition Temperature** : The lowest known value is 189°C (372.2°F) (DIPROPYLENE GLYCOL BUTYL ETHER).
- Flash Points** : Closed cup: >100°C (212°F).
- Flammable limits** : The greatest known range is Lower: 0.6% Upper: 20.4% (DIPROPYLENE GLYCOL BUTYL ETHER)
- Products of combustion** : These products are carbon oxides (CO, CO₂), nitrogen oxides (NO, NO₂...).
- Fire Hazards in Presence of Various Substances/Conditions** : Slightly flammable to flammable in presence of open flames, sparks and static discharge, of oxidizing materials.
- Explosion Hazards in Presence of Various Substances/Conditions** : Not available.
- Fire fighting media and instructions** : SMALL FIRE: Use DRY chemical powder.
LARGE FIRE: Use water spray, fog or foam. Do not use water jet.
- Protective clothing (fire)** : Be sure to use an approved/certified respirator or equivalent.

Section 6. Accidental release measures

- Spill and Leak** : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (Section 8).
If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Dispose of as in Section 13.

Section 7. Handling and storage

Handling : Do not ingest. Do not get in eyes, on skin or on clothing. Keep container closed when not in use. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling.

Storage : Keep container tightly closed. Keep container in a cool, well-ventilated area.

OTHER PRECAUTIONS: All precautions must be observed. Empty container may retain product residues.

Section 8. Exposure Controls, Personal Protection

Selection of personal protective equipment (PPE) is to be established by performing a PPE hazard assessment. In the U.S.A, OSHA requires completion of a certified PPE hazard assessment as described in 29 CFR 1910.132.

Engineering controls : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal protection

Eyes : Safety glasses.

Body : Synthetic apron.

Respiratory : Wear appropriate respirator when ventilation is inadequate.

Hands : Impervious gloves.

Feet : Not applicable.

Protective clothing (pictograms) :



HYGIENIC PRACTICES: Good personal hygiene practices are required at all times when handling chemicals. These practices include, but are not limited to, washing when safety equipment is removed, at the end of each shift or when going on breaks and especially if contamination occurs.

Section 9. Physical and chemical properties

Physical State and Appearance : Liquid.

Color : Not available.

Odor : Not available.

pH : Not available.

Boiling/condensation point : The lowest known value is 100°C (212°F) (WATER).

Melting/freezing point : May start to solidify at -59.95°C (-75.9°F) based on data for: 1,2-PROPANEDIOL.

Specific Gravity : Weighted average: 1 (Water = 1)

Vapor pressure : The highest known value is 2.3 kPa (17.5 mm Hg) (at 20°C) (WATER).

Vapor density : Lighter than air

Volatility : 100% (v/v). (WATER.) Weighted average: 100% (v/v) 100% (w/w). (WATER.) Weighted average: 99% (w/w).

Odor threshold : Not available.

Evaporation rate : The highest known value is Lower than 1. (WATER) compared to BUTYL ACETATE

VOC : 336 (g/l).

Solubility : Easily soluble in hot water.
Soluble in cold water, diethyl ether, acetone.
Insoluble in methanol.

Section 10. Stability and reactivity

- Stability and Reactivity** : The product is stable.
- Conditions of instability** : heat, open flame, sparks,
- Incompatibility with various substances** : Slightly reactive to reactive with oxidizing agents, reducing agents, acids, alkalis.
- Hazardous Reaction Products** : Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.
- Hazardous polymerization** : Will not undergo hazardous polymerization.

Section 11. Toxicological information

Toxicity data

<u>Ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
n-methyl pyrrolidone	LD50	3914 mg/kg	Oral	Rat
	LD50	8000 mg/kg	Dermal	Rabbit
	LC50	>400 ppm (4 hour(s))	Inhalation	Rat
butoxyethoxyethanol	LD50	5660 mg/kg	Oral	Rat
	LD50	4000 mg/kg	Dermal	Rabbit
1,2-propanediol	LD50	20000 mg/kg	Oral	Rat
	LD50	>2080 mg/kg	Oral	quail
	LD50	18350 mg/kg	Oral	Guinea pig
	LD50	20800 mg/kg	Dermal	Rabbit
	LC50	>105 ppm (8 hour(s))	Inhalation	Rat

Section 12. Ecological information

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
butoxyethoxyethanol	Lepomis macrochirus (LC50)	96 hour(s)	1300 mg/l
1,2-propanediol	Daphnia magna (EC50)	48 hour(s)	>10000 mg/l
	Pimephales promelas (LC50)	96 hour(s)	710 mg/l
	Pimephales promelas (LC50)	96 hour(s)	55770 mg/l
	Pimephales promelas (LC50)	96 hour(s)	>62000 mg/l

Products of degradation : These products are carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO₂...).

Toxicity of the products of biodegradation : The products of degradation are less toxic than the product itself.

Section 13. Disposal considerations

Waste information : The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

<u>Regulatory Information</u>	<u>UN number</u>	<u>Proper shipping name</u>	<u>Class</u>	<u>Packing group</u>	<u>Label</u>	<u>Additional information</u>
DOT Classification	Not available.	Not available.	Not available.	Not available.		Not available.
TDG Classification	Not available.	Not available.	Not available.	Not available.		Not available.

IMDG Class	Not available.	Not available.	Not available.	Not available.		Not available.
IATA-DGR Class	Not available.	Not available.	Not available.	Not available.		Not available.

Section 15. Regulatory information

U.S. Federal regulations : This product contains an exempt polymer under 40 CFR 723.250(60FR60; May 29, 1995). All other components are on the TSCA Inventory.

(HAPS) Clean air act (CAA) 112 regulated toxic substances: BUTOXYTRIETHYLENE GLYCOL; BUTOXYETHOXYETHANOL; 1,2-ETHANEDIOL; TRIETHYLAMINE

SARA 313

Form R - Reporting requirements : N-METHYL PYRROLIDONE 3.00 - 7.00
 BUTOXYETHOXYETHANOL 1.00 - 3.00

Supplier notification : No products were found.

State regulations : **WARNING:** This product contains chemical(s) known to the state of California to cause birth defects or other reproductive harm.: N-METHYL PYRROLIDONE

International regulations

International lists : This product contains one or more components that are NOT listed on the CEPA DSL inventory.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Fire hazard		1
Physical Hazard		0
Personal protection		



Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).
 Class D-2A: Material causing other toxic effects (VERY TOXIC).
 Class D-2B: Material causing other toxic effects (TOXIC).

Notice to reader

The absence of a positive finding indicates that we believe, to the best of our knowledge, that the negative is true.

Disclaimer: While Akzo Nobel Coatings believes that the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which Akzo Nobel Coatings assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, Provincial and local laws and regulations.